

Can. to JP 11-514827


PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6: H04J 11/00	A2	(11) International Publication Number: WO 98/10542
		(43) International Publication Date: 12 March 1998 (12.03.98)
(21) International Application Number: PCT/FI97/00525		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).
(22) International Filing Date: 5 September 1997 (05.09.97)		
(30) Priority Data: 963479 5 September 1996 (05.09.96) FI		
(71) Applicant (for all designated States except US): NOKIA TELECOMMUNICATIONS OY (FI/FI); Keilalahdentie 4, FIN-02150 Espoo (FI).		
(72) Inventors; and (75) Inventors/Applicants (for US only): HÄKKINEN, Hannu (FI/FI); Vuokselantie 10 B, FIN-02140 Espoo (FI). HOTTINEN, Ari (FI/FI); Kielatie 30-32 C 25, FIN-01300 Vantaa (FI). KOKKONEN, Mikko (FI/FI); Isokari 15 a B 32, FIN-00200 Helsinki (FI). WICHMAN, Risto (FI/FI); Ilmarinkatu 16 B 7, FIN-00100 Helsinki (FI).		
(74) Agent: PATENTTITOIMISTO TEKNOPOUS KOLSTER OY; c/o Kolster Oy Ab, Iso Roobertinkatu 23, P.O. Box 148, FIN-00121 Helsinki (FI).		Published In English translation (filed in Finnish). Without international search report and to be republished upon receipt of that report.

(54) Title: TRANSMITTING AND RECEIVING METHOD AND RADIO SYSTEM



(57) Abstract

The invention relates to a transmitting and receiving method and a radio system. In a transmitter (TR) the signals (37) to be transmitted are spread coded in means (31) and modulated by subcarriers in means (33). In a receiver (R) the signals are demodulated in means (35) and submitted to multiuser detection in means (36) by using the subcarriers to limit the number of detectable signals in the means (35). The receiver (R) uses multiuser detection for reducing multiple access interference and correcting frequency-selective fading.